

VANDER-LIFT II SPECIFICATIONS

MODEL B450

CONSTRUCTION

- ◆ Smooth electric wormgear (not hydraulic) lift drive
- ◆ Controller is hand held, push button up/down
- ◆ Controller secures on the lifter frame
- ◆ Auxiliary down switch, mounted on control box
- ◆ Manual emergency down
- ◆ 3" dual front casters, 4" single rear locking casters - Standard (low and high options available)
- ◆ Padded hanger assembly
- ◆ Welded steel (no aluminum)-baked on, chip and rust resistant finish
- ◆ Battery powered with 24 volt rechargeable "memory free" batteries
- ◆ Battery recharger unit with overcharging protection
- ◆ Approximately 150 transfers per charge
- ◆ Recharge time 6-10 hours
- ◆ Low battery audible and light indication

LIFT

- ◆ Manual base expands easily to accommodate bed, chair, toilet or tub, or most specialized equipment
- ◆ Clears most under-bed frames, including Clinitron beds, Styrker frames and tilt tables. Optional caster sizes available to adjust base height
- ◆ Lifts high enough to access all known beds/tables, etc.
- ◆ Able to tend to the patient with hands-on care while lifter is raising/lowering
- ◆ Full control of patient positioning into chairs/beds, etc
- ◆ Maximum lifting capacity 450 lbs.
- ◆ Lift weight: 103 lbs

SLING

- ◆ Sling stays with the lifter when transfer is complete with optional sling bag
- ◆ Easily positioned **without having to get in under** the patients pelvis
- ◆ Sling sizes from small to xx-large
- ◆ Custom slings available for individual resident/patient needs
- ◆ Allows toileting without soiling the sling
- ◆ No chains or metal supports
- ◆ Built in head support
- ◆ Variety of sling materials including disposable, mesh and high heat laundering
- ◆ Slings available to accommodate contractures, amputees and rigid patients, also quadriplegic, and comatose
- ◆ 4 point sling hookup for maximum versatility, safety and comfort

DIMENSIONS

- ◆ Overall width – legs closed, 26"
- ◆ Overall width – legs open, 44 ½"
- ◆ Boom – maximum height 73"
- ◆ Chassis – length 47 ½"
- ◆ Chassis – height 4 ¼"
- ◆ Casters – wheel diameter 3"
- ◆ Height – top of tower 53 ¾"