

MODEL 600
THE VANDER-LIFT SPECIFICATIONS

CONSTRUCTION

- ◆ smooth electric wormgear (not hydraulic) lift drive
- ◆ controller is hand held, push button up/down
- ◆ back of controller magnetized; secures anywhere on the lifter frame
- ◆ auxiliary up/down toggle switch, mounted on lift base
- ◆ 3" dual front casters, 4" single rear locking casters - Standard (low and high options available)
- ◆ fully padded head area
- ◆ welded steel (no aluminum)-baked on, chip and rust resistant finish
- ◆ battery powered with 24 volt rechargeable "memory free" batteries
- ◆ built-in battery recharger unit-includes built-in overcharging protection
- ◆ approximately 150 transfers per charge
- ◆ recharge time- 6-10 hours
- ◆ low battery indicator light
- ◆ battery charging indicator light

LIFT

- ◆ base expands easily to accommodate bed, chair, toilet or tub, or most specialized equipment
- ◆ clears all under-bed frames including Clinitron beds, Stryker frames and tilt tables
- ◆ lifts high enough to access all beds/tables, etc.
- ◆ able to tend to the patient with hands-on care while lifter is raising/lowering
- ◆ full control of patient positioning into chairs/beds, etc.
- ◆ maximum lifting capacity 600 pounds
- ◆ most lifts require one attendant
- ◆ Lift weight: 122 lbs

SLING

- ◆ sling stays with the lifter when transfer is complete
- ◆ easily positioned **without having to get it under** the patient's pelvis
- ◆ four sling sizes - small, medium, large, jumbo size available to 600 pounds
- ◆ allows toileting without soiling the sling
- ◆ no chains or metal supports
- ◆ built in head support
- ◆ machine washable – long wearing
- ◆ accommodates contractures, amputees and rigid patients, also quadriplegic, and comatose
- ◆ 4 point sling hookup for maximum versatility, safety and comfort

DIMENSIONS

- ◆ overall width – legs closed, 31"
- ◆ overall width – legs open, 45"
- ◆ boom – maximum height, 81 ½"
- ◆ boom – length, 37"
- ◆ chassis – length, 50 ¼"
- ◆ chassis – height, 4 ¼"
- ◆ casters – wheel diameter, 3"
- ◆ height – top of tower, 57 ¾"