

VERA LIFT SPECIFICATIONS

MODEL V600

CONSTRUCTION

- ◆ Smooth, electric worm-gear lift drive (not hydraulic, chain or belt driver).
- ◆ Hand-held controller (push-button operated, heavy duty coil cord, operable with single finger touch, magnetized so as to secure anywhere on the lifter frame).
- ◆ Back-up safety switches on lift base (up/down control and manual shut-off).
- ◆ 3" dual front casters, 4" single rear locking casters - Standard (low and high options available)

- ◆ Fully-padded, patient contact points.
- ◆ Welded steel (no aluminum); chip, peel and rust proof hammertone finish; no painted or plastic coatings on steel components.
- ◆ 24 volt, rechargeable "memory free" batteries, gel-cel (not lead acid).
- ◆ Built in battery charger (in the lift base) with overcharging protection; approximately 125-150 transfers per charge; recharge time (15 minute quick charge) and 6-8 hours full charge.

LIFT

- ◆ Fixed mast with pivoting boom.
- ◆ Expandable base; hand-lever activated to accommodate bed, chair, toilet, or most specialized equipment.
- ◆ Capacity to clear all under-bed frames.
- ◆ Height-adjustable foot and knee rest with leg support strap.
- ◆ Large lifting capacity, up to 600 pounds.
- ◆ Ability to maneuver through small doorways and bathrooms.
- ◆ Lift weight: 144 lbs

BACK BELTS

- ◆ Detach from the lifter when transfer is complete.
- ◆ Accommodate 50 to 600 pound residents (four sizes of belts).
- ◆ Allow toileting without soiling the sling.
- ◆ Use no chains or metal support.
- ◆ Provide safety strap for patient's chest with easy press-to-release buckle.
- ◆ Are machine washable (up to 180⁰ F), quick drying, conveniently stored in pouches.

DIMENSIONS

- ◆ Overall width with legs closed 30 5/8"
- ◆ Overall width with legs open 44"
- ◆ Chassis height 4 1/4"
- ◆ Chassis length 49 5/8"
- ◆ Height to top of tower 51"